

EZYFLEX® EI EPDM hose with stainless steel braid DN08





FT101a

Composition: Technical data **Sanitary** • EPDM tube according to EN 681-1 type WB • AISI 304 stainless steel braid Maximum temperature Taps and sanitary • Nickel-plated brass fittings +90°C (peaks to +110°C) appliances • Stainless steel crimping bushings Sealing: Max operating pressure 16 bar • Flat gasket on flat seat • O-ring on metric male thread • Barbed fitting for smooth tube for dual-taper fitting 8.5 x 12 mm (DN08) Standard lengths: 150, 300, 500, 700, 1000 mm Minimum bending radius 48 mm hannan Application: Hot and cold water supply for taps, mixers and sanitary appliances CUSTOM OFFER Specific length: 150 mm to over 10,000 mm MOQ depending on the desired length > Customisable fittings: diameter, material, etc.

Customisable packaging: contact us

Taps

Assembled hoses / References & Configurations

Reference	Hose	Fitting 1 / Thread		Fitting 2 / Thread	
EI08P1M10		Female	3/8"	Short male	M10x100
EI08P1M11					M11x100
EI08P1M12					M12x100
EI08P2M10			1/2″		M10x100
EI08P1M10		Female	3/8"	Long male	M10x100
EI08P1M11					M11x100
EI08P1M12					M12x100
EI08P2M10			1/2"		M10x100



www.flexibles.com

IFT Groupe Omerin SAS Zone Industrielle – F 63600 Ambert Tel: +33 (0)4 73 82 32 33 ift@omerin.com

14

The information provided on this data sheet is indicative and subject to change without notice. All hoses ordered must comply with IFT's installation recommendations, which can be viewed in its catalogue. IFT can under no circumstances be held liable for any incidents arising from inappropriate use, particularly in the case of installation not carried out in accordance with the rules of the trade and the standards in force. Registered trademark of IFT. Drawings and photos are not contractually binding. Reproduction is prohibited without the prior consent of IFT.

Q CUSTOM OFFER

- Specific length: 150 mm to over 10,000 mm MOQ depending on the desired length
- ▶ Packaging customisation → Contact us
- **Customisable fittings** Diameter, Material, etc.

Sanitary appliances

Assembled hoses / References & Configurations

Reference	Hose	Fitting 1 / Thread		Fitting 2 / Thread	
EI08P1M1			3/8"		3/8"
EI08P2M2	-8	Female	1/2"	Male	1/2"
EI08P4M4			3/4"		3/4"
EI08P1P1	-6	Female	3/8"	Female	3/8"
EI08P2P2			1/2"		1/2"
E108P4P4			3/4"		3/4"
EI08P1C1		Female	3/8"	Angled	3/8"
EI08P2C2			1/2"		1/2"
EI08P4C4			3/4"		3/4"
EI08M1B1		Male	3/8"	Dual-taper	Ø10 mm
EI08M2B2			1/2"		Ø12 mm
EI08M4B3			3/4"		Ø14 mm
EI08P1B1		Female	3/8"	Dual-taper	Ø10 mm
EI08P2B2			1/2"		Ø12 mm
EI08P4B3			3/4"		Ø14 mm
EI08B1B1		Dual-taper	Ø10 mm	Dual-taper	Ø10 mm
EI08B2B2			Ø12 mm		Ø12 mm
EI08B3B3			Ø14 mm		Ø14 mm



IFT Groupe Omerin SAS Zone Industrielle – F 63600 Ambert Tel: +33 (0)4 73 82 32 33 ift@omerin.com

www.flexibles.com

The information provided on this data sheet is indicative and subject to change without notice. All hoses ordered must comply with IFT's installation recommendations, which can be viewed in its catalogue. IFT can under no circumstances be held liable for any incidents arising from inappropriate use, particularly in the case of installation not carried out in accordance with the rules of the trade and the standards in force. Registered trademark of IFT. Drawings and photos are not contractually binding. Reproduction is prohibited without the prior consent of IFT.