



# EZYFLEX® EC

## EPDM hose with stainless steel braid with PVC coating DN10 and 12



### Sanitary

Wash shower heads for the public sector and hospitals



#### ► Composition:

- EPDM tube according to EN 681-1 type WB
- AISI 304 stainless steel braid
- Smooth crystal-clear PVC exterior coating
- Nickel-plated brass fittings
- Shower head-side anti-twist system
- Stainless steel crimping bushings

#### ► Sealing:

- Flat gasket on flat seat
- O-ring on metric male thread

#### ► Standard lengths:

Custom-made

#### ► Application:

Hot and cold water supply wash shower heads for the public sector and hospitals

#### ► Technical data



Maximum temperature  
**+60°C**



Max operating pressure **10 bar**



**9,5 x 16 mm (DN10)**  
**12 x 20 mm (DN12)**



Min bending radius  
**60 mm (DN10)**  
**72 mm (DN12)**







This hose can be cleaned  
with all detergents



#### CUSTOM OFFER

- Specific length: **150 mm to over 10,000 mm**  
MOQ depending on the desired length
- Customisable fittings: diameter, material, etc.
- Customisable packaging: contact us

#### ► Assembled hoses / References & Configurations

Reference	DN (mm)	Hose	Fitting 1 / Thread		Fitting 2 / Thread	
EC10P2D2	10		Female	1/2"	Female Self-turning	1/2"
EC12P2D2	12					
EC10D2M15	10		Female Self-turning	1/2"	Male	15x100
EC10P1P1	10		Female	3/8"	Female	3/8"
EC10P2P2				1/2"		1/2"
EC12P2P2	12			3/4"		3/4"
EC12P4P4				3/4"		3/4"
EC10P1M1	10		Female	3/8"	Male	3/8"
EC10P2M2				1/2"		1/2"
EC12P2M2	12			3/4"		3/4"
EC12P4M4				3/4"		3/4"



IFT Groupe Omerin SAS  
Zone Industrielle - F 63600 Ambert  
Tel: +33 (0)4 73 82 32 33  
ift@omerin.com

[www.flexibles.com](http://www.flexibles.com)

The information provided on this data sheet is indicative and subject to change without notice. All hoses ordered must comply with IFT's installation recommendations, which can be viewed in its catalogue. IFT can under no circumstances be held liable for any incidents arising from inappropriate use, particularly in the case of installation not carried out in accordance with the rules of the trade and the standards in force. © Registered trademark of IFT. Drawings and photos are not contractually binding. Reproduction is prohibited without the prior consent of IFT.