

DrainageWashing machines, drain hoses and siphons



Drainage hose for washing machines or dishwashers

▶ **Assembled hoses /** References & Configurations

Reference	DN (mm)	Fittings	
FE20PP	20	Flexible push-in heat-sealed end pieces	

▶ Composition:

- Corrugated PP tube
- EPDM thermoplastic rubber fittings
- > Standard lengths:

1500 mm

▶ Technical data



Maximum temperature

+95°C



Hose type "drain hose" for bidets, washing machines or dishwashers

▶ **Assembled hoses /** References & Configurations

Reference	DN (mm)	Fittings
FE20PP-EX	20	Flexible push-in heat-sealed end pieces



- Corrugated PP tube
- EPDM thermoplastic rubber fittings
- Standard lengths (min / max):

800 / 2700 mm, 1200 / 4000 mm

▶ Technical data



Maximum temperature

+95°C



Stretch



"Siphon" type hose for bidets, washbasins and sinks

> Assembled hoses / References & Configurations

Reference	DN (mm)	Fitting 1 / Thread		Fitting 2
FE33P6M32	33	Female swivel nut	1"1/4	Male PVC glue-on Ø 32 mm
FE40P7M40	40	Flexible push-in heat-sealed end pieces	1"1/2	Male PVC glue-on Ø 40 mm

Composition:

- PVC hose
- PVC swivel nut fitting and glue-on male end piece
- Standard lengths (min / max):

350 / 700 mm

▶ Technical data



Maximum temperature

+90°C



Stretch



IFT Groupe Omerin SAS Zone Industrielle – F 63600 Ambert Tel: +33 (0)4 73 82 32 33 ift@omerin.com

www.flexibles.com

The information provided on this data sheet is indicative and subject to change without notice. All hoses ordered must comply with IFT's installation recommendations, which can be viewed in its catalogue. IFT can under no circumstances be held liable for any incidents arising from inappropriate use, particularly in the case of installation not carried out in accordance with the rules of the trade and the standards in force. Registered trademark of IFT. Drawings and photos are not contractually binding. Reproduction is prohibited without the prior consent of IFT.