



EZYFLEX® NI

Nitrile NBR hose with stainless steel braid

DN08 to 33

Heating

Oil and hydrocarbon burners



► Composition:

- Nitrile NBR tube
- AISI 304 stainless steel braid with blue or yellow edging
- Brass fittings (nickel-plated brass for angled fitting)
- Stainless steel crimping bushings

► Sealing:

- Metal / Metal on spherical-tapered seat

► Standard lengths:

300, 500, 700, 1000 mm

► Application:

Compressed air, gas oil, etc.
supply for oil and hydrocarbon burners

► Technical data



Maximum temperature
+90°C



Max operating pressure
16 Bar (DN08 and 15)
10 Bar (DN20)
6 Bar (DN26 and 33)



7.7 x 12 mm (DN08) **20 x 28 mm (DN20)**
9.5 x 14 mm (DN10) **26 x 35 mm (DN26)**
12 x 18 mm (DN12) **33 x 43 mm (DN33)**
15 x 22 mm (DN15)



CUSTOM OFFER

- Specific length: **150 mm to over 10,000 mm**
MOQ depending on the desired length
- Customisable fittings: diameter, material, etc.
- Customisable packaging: contact us

► Assembled hoses / References & Configurations

Reference	DN (mm)	Hose	Fitting 1 / Thread		Fitting 2 / Thread		Bending radius (mm)	
NI08S0S0	08		Female spherical tapered	1/4"	Female spherical tapered	1/4"	48	
NI08S0S1				1/4"		3/8"		
NI08S1S1				3/8"		3/8"		
NI10S1S1				3/8"		3/8"		60
NI12S2S2				1/2"		1/2"		72
NI15S2S2				1/2"		1/2"		88
NI20S4S4				3/4"		3/4"		112
NI26S5S5				1"		1"		140
NI33S6S6				1"1/4		1"1/4		172
NI08S0Y0	08		Female spherical tapered	1/4"	Male tapered	1/4"	48	
NI08S0Y1				1/4"		3/8"		
NI08S1Y1				3/8"		3/8"		60
NI10S1Y1				3/8"		3/8"		72
NI12S2Y2				1/2"		1/2"		88
NI15S2Y2				3/4"		3/4"		112
NI20S4Y4				1"		1"		140
NI26S5Y5				1"1/4		1"1/4		172
NI33S6Y6				1"1/4		1"1/4		172
NI08S0W0	08		Female spherical tapered	1/4"	Angled spherical tapered	1/4"	48	
NI08S0W1				1/4"		3/8"		
NI08S1W0				3/8"		1/4"		
NI08S1W1				3/8"		3/8"		
NI10S1W1				3/8"		3/8"	60	
NI12S2W2				1/2"		1/2"	72	
NI15S2W2				3/4"		3/4"	88	
NI20S4W4				1"		1"	112	
NI26S5W5				1"1/4		1"1/4	140	
NI33S6W6				1"1/4		1"1/4	172	