



EZYFLEX® FE

Stainless steel corrugated hose DN10 to 50

Heating

Steam supply



► Composition:

- AISI 304L stainless steel corrugated tube
- AISI 303 stainless steel fittings
- AISI 303 stainless steel fittings welded under argon

► Standard lengths: (min / max)

75/130 mm, 100/200 mm, 200/400 mm,
260/520 mm, 500/1000 mm,
750/1500 mm, 1000/2000 mm

► Application:

Steam, hot and cold water supply for heating appliances

► Technical data



Maximum temperature
+90°C



Maximum operating pressure for gas
0.5 Bar

Max operating pressure for water
10 Bar (DN10)
8 Bar (DN15, 20, 26)
5 Bar (DN33, 40, 50)





Can stretch up to twice
the initial length



CUSTOM OFFER

- Specific length: **150 mm to over 10,000 mm**
MOQ depending on the desired length
- Customisable fittings: diameter, material, etc.
- Customisable packaging: contact us

► Assembled hoses / References & Configurations

Reference	DN (mm)	Hose	Fitting 1 Thread		Fitting 2 Thread	
FE10P1M1	10		Female	3/8"	Male	3/8"
FE15P2M2	15			1/2"		1/2"
FE15P4M2				3/4"		1/2"
FE20P4M4	20			3/4"		3/4"
FE26P5M5	26			1"		1"
FE33P6M6	33			1"1/4		1"1/4
FE40P7M7	40			1"1/2		1"1/2
FE50P8M8	50			2"		2"
FE15P2P2	15		Female	1/2"	Female	1/2"
FE20P4P4	20			3/4"		3/4"
FE26P5P5	26			1"		1"