



CLIMFLEX® EI

EPDM hose with stainless steel braid DN10, 12 and 15



Chilled ceilings



► Safety clips (OPTIONAL) / References

Reference	For copper tube Diameter (mm)
CLIPS12	12
CLIPS15	15



► Composition:

- EPDM tube according to EN 681-1 type WB
- AISI 304 stainless steel braid
- Brass fittings
- Stainless steel crimping bushings

► Sealing:

- Flat gasket on flat seat
- integrated DN10 and 12
- optional DN15

► Safety:

Optional safety clips for quick coupling

► Lengths:

Custom-made

► Application:

Hot and chilled water supply to chilled ceilings - Chilled beams - Velums.
If chilled water (temp. Below dew point):
contact us for insulation requirements.

► Technical data

Minimum temperature

-15°C

Maximum temperature
+90°C



Glycol water flow rate up to 40%
(for larger capacities, contact us)



9.5 x 14 mm (DN10)

12 x 18 mm (DN12)

15 x 22 mm (DN15)



CUSTOM OFFER

- Specific length: **150 mm to over 10,000 mm**
MOQ depending on the desired length
- Customisable fittings: diameter, material, etc.
- Customisable packaging: contact us

► Assembled hoses / References & Configurations

Reference	DN (mm)	Hose	Fitting 1 Thread		Fitting 2 Thread		Bending radius (mm)
EI10I0I0	10		Quick	Ø 10 mm	Quick	Ø10mm	60
EI12I1I1	12			Ø 12 mm		Ø12 mm	72
EI12I2I2				Ø 15 mm		Ø15 mm	
EI15I2I2	15			Ø 15 mm		Ø15 mm	88
EI10P1I0	10		Female	3/8"	Quick	Ø10 mm	60
EI10P2I0	10			1/2"		Ø10 mm	60
EI12P2I1	12			1/2"		Ø12 mm	72
EI12P2I2				1/2"		Ø15 mm	88
EI15P2I2	15			1/2"		Ø15 mm	88
EI10P2C0	10		Female	1/2"	Quick Angled	Ø10 mm	60
EI10P2C1						Ø12 mm	
EI12P2C1	12					Ø12 mm	72
EI12P2C2						Ø15 mm	88
EI15P2C2	15					Ø15 mm	88