



Specific applications

▶ Composition:

- Silicone tube (food grade) translucent or coloured
- AISI 304 stainless steel braid

▶ Lengths:

Custom-made

▶ Diameters:

DN06 to 26

► Application:

- Food-grade: all foods and beverages, vegetable and animal oils
- Industry: certain aggressive products such as citric or tartaric acid, alcohols, etc.
- Compressor outputs (industrial quality)
- High temperatures

▶ Technical data



Operating temperature -80°C to +200°C



Max operating pressure 16 Bar (DN08 to 15) 10 Bar (DN20) 6 Bar (DN26)



KEY BENEFITS

- Excellent corrosion resistance and ageing resistance
- ► High flexibility
- ➤ Resistant to high temperatures
- ► Absorbs expansion and water hamme
- Accidental abrasion resistance
- Good resistance to aggressive fluids, alcohols and acids

- ➤ Does not transmit hose noise
- ➤ Good UV resistance
- * Tube material FDA 21 CFR 177.2600 approved European Regulation 1935/2004, European Pharmacopoeia section 3.1.9

➤ Assembled hoses / Hose & Connection references

Reference of the hose	DN (mm)	Diameter int. x ext. (mm)	Min bending radius (mm)
SI 08	08	8 x 12.8	55
SI 10	10	10 x 14.8	70
SI 12	12	12 x 17.8	85
SI 15	15	15 x 21.8	120
SI 20	20	20 x 28	200
SI 25	26	25 x 33	300