



QUAL'IFT® NI

Specific Nitrile NBR hose
with stainless steel braid

Specific applications



- ▶ **Composition:**
 - Nitrile NBR tube
 - AISI 304 stainless steel braid with distinctive blue or yellow edging (other colours on request)
- ▶ **Lengths:**
 - Custom-made
- ▶ **Diameters:**
 - DN06 to 33
- ▶ **Application:**
 - Industry: fuel oil, diesel, oils, greases, compressed air, regulation, natural gas, LPG, etc.

- ▶ **Technical data**
-  Operating temperature **-10°C to +90°C (peaks at 100°C)**
-  Max operating pressure **16 Bar (DN06 to 15)**
10 Bar (DN20)
6 Bar (DN26 and 33)



KEY BENEFITS

- ▶ Excellent corrosion and ageing resistance
- ▶ Accidental abrasion and alternating stresses resistance
- ▶ Hoses tested according to ISO 6806 type 1

▶ Assembled hoses / Hose & Connection references

Reference of the hose	DN (mm)	Diameter int. x ext. (mm)	Min bending radius (mm)
NI 06	06	5.5 x 10	40
NI 08	08	7.5 x 12	48
NI 10	10	9.5 x 14	60
NI 12	12	12 x 18	72
NI 15	15	15 x 22	88
NI 20	20	20 x 28	112



IFT Groupe Omerin SAS
Zone Industrielle - F 63600 Ambert
Tel: +33 (0)4 73 82 32 33
ift@omerin.com

www.flexibles.com

The information provided on this data sheet is indicative and subject to change without notice. All hoses ordered must comply with IFT's installation recommendations, which can be viewed in its catalogue. IFT can under no circumstances be held liable for any incidents arising from inappropriate use, particularly in the case of installation not carried out in accordance with the rules of the trade and the standards in force. © Registered trademark of IFT. Drawings and photos are not contractually binding. Reproduction is prohibited without the prior consent of IFT.