


**QUAL'IFT® EI**
**EPDM hose with stainless steel braid DN08 to 50**

**► Composition:**

- EPDM tube according to EN 681-1 type WB
- AISI 304 stainless steel braid

**► Lengths:**

See table below

**Roll packaging**

(other types of packaging on request)

**► Application:**

- Water flow for sanitary, heating and air-conditioning applications (max glycol content : 40%)
- Aqueous solutions

**► Technical data**

 Operating temperature  
**-15°C to +90°C peaks at +110°C**

 Max operating pressure  
**16 Bar (DN08 to 15)**  
**10 Bar (DN20 and 26)**  
**6 Bar (DN33 to 50)**


See table below


**KEY BENEFITS**

- Excellent corrosion and ageing resistance
- Absorbs expansion and water hammer
- Accidental abrasion resistance
- Good UV resistance
- Does not transmit hose noise


**ASSEMBLY**

- **QUAL'IFT®** hoses must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"


**CUSTOM OFFER**

- Contact us for all your specific requirements

**► Hoses for your low-pressure applications / References**

Reference	DN (mm)	Diameter int. x ext. (mm)	Burst pressure (Bar)	MOQ (m)	Bending radius (mm)
EI 08	08	8.5 x 12	110	25	48
EI 10	10	9.5 x 14			60
EI 12	12	12 x 18	90	25	72
EI 15	15	15 x 22	80	25	88
EI 20	20	20 x 28	60	20	112
EI 26	26	26 x 35	45	30	140
EI 33	33	33 x 43	40	20	172
EI 40	40	40 x 50	30	Contact us	392
EI 50	50	50 x 63			488