



QUAL'IFT® NI

Nitrile hose with stainless steel braid DN06 to 33



► Composition:

- Nitrile NBR tube
- AISI 304 stainless steel braid with blue or yellow edging (other edging colours on request MOQ on request)

► Lengths:

See table below

Roll packaging

(other types of packaging on request)

► Application:

- Transport of fuel oil, diesel, oils and greases, compressed air, natural gas, LPG, etc.

► Technical data



Operating temperature
-15°C to +90°C peaks at +110°C



Max operating pressure
16 Bar (DN06 to 15)
10 Bar (DN20)
6 Bar (DN26 and 33)



See table below



Excellent resistance
to hydrocarbons



KEY BENEFITS

- Excellent corrosion and ageing resistance
- **Excellent resistance to hydrocarbons**
- Absorbs expansion and water hammer
- Accidental abrasion and alternating stress resistance
- Good UV resistance
- Does not transmit hose noise



ASSEMBLY

► **QUAL'IFT®** hoses must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"



CUSTOM OFFER

- Contact us for all your specific requirements

► Hoses for your low-pressure applications / References & Compositions

Reference	DN (mm)	Diameter int. x ext. (mm)	Burst pressure (Bar)	MOQ (m)	Bending radius (mm)
NI 06	06	5.5 x 10	110	25	40
NI 08	08	7.5 x 12			48
NI 10	10	9.5 x 14			60
NI 12	12	12 x 18	90	25	72
NI 15	15	15 x 22	80	25	88
NI 20	20	20 x 28	60	25	112
NI 26	26	26 x 35	45	25	140
NI 33	33	33 x 43	40	Contact us	172