



# QUAL'IFT® EIC

## EPDM hose with stainless steel braid and PVC coating DN10 to 12



### ► Composition:

- EPDM tube according to EN 681-1 type WB
- AISI 304 stainless steel braid
- Crystal PVC coating

### ► Lengths:

See table below

### Roll packaging

(other types of packaging on request)

### ► Application:

- Pressurised water transport for cleaning in the public sector, hospitals and the food industry

### ► Technical data



Operating temperature  
**-15°C to +60°C**



Max operating pressure  
**16 Bar**



See table below



### KEY BENEFITS

- Excellent corrosion and ageing resistance
- Easy maintenance
- Excellent abrasion resistance
- Absorbs expansion and water hammer
- Good UV resistance
- Does not transmit hose noise



### ASSEMBLY

- **QUAL'IFT®** hoses must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"



### CUSTOM OFFER

- Contact us for all your specific requirements

### ► Hoses for your low-pressure applications / References & Compositions

Reference	DN (mm)	Diameter int. x ext. (mm)	Burst pressure (Bar)	MOQ (m)	Bending radius (mm)
EIC 10	10	9.5 x 16	110	25	60
EIC 12	12	12 x 20	90		72