



# QUAL'IFT® ET

## EPDM hose with polyester braid DN08 to 50



### ► Composition:

- EPDM tube according to EN 681-1 type WB
- Stiff polyester braid

### ► Lengths:

See table below

### Roll packaging

(other types of packaging on request)

### ► Application:

- Water passage for sanitary, heating and air conditioning (max glycol content : 40%)
- Aqueous solutions

### ► Technical data



Operating temperature  
**-15°C to +90°C peaks at +110°C**



Max operating pressure  
**16 Bar (DN08 to 15)**  
**10 Bar (DN20 and 26)**  
**6 Bar (DN33 to 50)**



See table below



### KEY BENEFITS

- Excellent corrosion and ageing resistance
- Absorbs expansion and water hammer
- Accidental abrasion resistance
- Does not transmit hose noise



### ASSEMBLY

- **QUAL'IFT®** hoses must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"



### CUSTOM OFFER

- Contact us for all your specific requirements

### ► Hoses for your low-pressure applications / References & Compositions

Reference	DN (mm)	Diameter int. x ext. (mm)	Burst pressure (Bar)	MOQ (m)	Bending radius (mm)
ET 08	08	8.5 x 12	110	25	48
ET 10	10	9.5 x 14			60
ET 12	12	12 x 18	90	25	72
ET 15	15	15 x 22	80	25	88
ET 20	20	20 x 28	60	20	112
ET 26	26	26 x 35	45	30	140
ET 33	33	33 x 43	40	20	172
ET 40	40	40 x 50	30	Contact us	392
ET 50	50	50 x 63			488