



PSM fitting

Female with spherical-tapered seat



► Composition:

- Brass
- Gas thread according to ISO 228
- Other materials on request (nickel-plated brass, stainless steel, etc.)

► Packaging:

- In bags
- Other packaging types on request

► Assembly:

PSM fittings can be used on our QUAL'IFT® hoses (according to the indications in the table below)

► Sealing:

Metal / Metal

► Application:

All low-pressure applications

ASSEMBLY

► IFT fittings must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"



CUSTOM OFFER

► Contact us for all your specific requirements

► Fittings for your low-pressure applications / References & Compositions

Without integrated gasket						With integrated gasket					
Reference	For hose	Material	Thread		Diam.	Reference	For hose	Material	Thread		Diam.
	DN (mm)		mm	thumb	mm		DN (mm)		mm	thumb	mm
PSM060LAELA	06	Brass	8 x 13	1/4"	4.8	PSM154LAELAJ	15	Brass	20 x 27	3/4"	12.5
PSM061LAELA			12 x 17	3/8"							
PSM080LAELA	08		8 x 13	1/4"	6.2						
PSM081LAELA			12 x 17	3/8"							
PSM101LAELA	10		12 x 17	3/8"	7						
PSM102LAELA			15 x 21	1/2"							
PSM121LAELA	12		12 x 17	3/8"	9.5						
PSM122LAELA			15 x 21	1/2"							
PSM124LAELA			20 x 27	3/4"							
PSM152LAELA	15		15 x 21	1/2"	12.5						
PSM204LAELA	20		20 x 27	3/4"	17						
PSM205LAELA			26 x 34	1"							
PSM265LAELA	26		26 x 34	1"	22						
PSM336LAELA	33		33 x 42	1"1/4	29						
PSM407LAELA	40		40 x 49	1"1/2	34.5						