



# M fitting

## Male fixed cylindrical



### ► Composition:

- Brass
- Gas thread according to ISO 228
- Other materials on request (nickel-plated brass, stainless steel, etc.)

### ► Packaging:

- In bags
- Other packaging types on request

### ► Assembly:

M fittings can be used on our QUAL'IFT® hoses (according to the indications in the table below)

### ► Sealing:

Flat gasket on flat seat

### ► Application:

All low-pressure applications



## ASSEMBLY

► IFT fittings must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"



## CUSTOM OFFER

► Contact us for all your specific requirements

### ► Fittings for your low-pressure applications / References & Compositions

Reference	For hose	Material	Thread		Diameter
	DN (mm)		mm	thumb	mm
M080NIB	08	Nickel-plated brass	8 x 13	1/4"	6.2
M081NIB			12 x 17	3/8"	
M082NIB			15 x 21	1/2"	
M101NIB	10		12 x 17	3/8"	7
M102NIB			15 x 21	1/2"	
M104NIB			20 x 27	3/4"	
M121NIA	12		12 x 17	3/8"	9.5
M122NIB			15 x 21	1/2"	
M124NIB			20 x 27	3/4"	
M152LAC	15	Brass	15 x 21	1/2"	12.5
M154LAC			20 x 27	3/4"	
M202LAA	20		15 x 21	1/2"	17
M204LAC			20 x 27	3/4"	
M205LAC			26 x 34	1"	
M265LAC	26		26 x 34	1"	22
M266LAA			33 x 42	1"1/4	
M336LAA	33		33 x 42	1"1/4	28
M337LAA			40 x 49	1"1/2	
M407LAA	40		40 x 49	1"1/2	34.5
M508LAA	50		50 x 60	2"	44



IFT Groupe Omerin SAS  
Zone Industrielle - F 63600 Ambert  
Tel: +33 (0)4 73 82 32 33  
ift@omerin.com