

RCPS **fitting** Female angled 90° with spherical-tapered seat





Composition:

- Brass or nickel-plated brass
- Gas thread according to ISO 228
- Other materials on request
- (nickel-plated brass, stainless steel, etc.)

Packaging: In bags

• Other packaging types on request

Assembly:

RCPS fittings can be used on our QUAL'IFT® hoses (according to the indications in the table below)

FT832a

> Sealing:

Metal / Metal

Application:

All low-pressure applications



IFT fittings must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"



Contact us for all your specific requirements

Fittings for your low-pressure applications / References & Compositions

Without integrated gasket							With integrated gasket							
Reference	For hose	Material		Thread		Diam.	Reference	For hose		Material		Thread		Diam.
	DN (mm)	Hose connection	Nut	mm	inches	mm	Reference	DN (mm)	Hose connection	Nut	mm	inches	mm	
RCPS080NIENI		Nickel-plated brass	Nickel- plated brass	8 x 13	1/4"	6.2	RCPS154LAELAJ	15	Brass	Brass	20 x 27	3/4"	12.5	
RCPS081NIENI	08			12 x 17	3/8"									
RCPS152LAELA	15	Brass	Brass	15 x 21	1/2"	12.5								
RCPS204LAELA	20			20 x 27	3/4"	17								



ift@omerin.com www.flexibles.com

IFT Groupe Omerin SAS Zone Industrielle – F 63600 Ambert Tel: +33 (0)4 73 82 32 33

The information provided on this data sheet is indicative and subject to change without notice. All hoses ordered must comply with IFT's installation recommendations, which can be viewed in its catalogue. IFT can under no circumstances be held liable for any incidents arising from inappropriate use, particularly in the case of installation not carried out in accordance with the rules of the trade and the standards in force. Registered trademark of IFT. Drawings and photos are not contractually binding. Reproduction is prohibited without the prior consent of IFT.