



# UMM fitting

## Male-Male Union with flat seat



### ► Composition:

- Brass
- A gas thread according to ISO 228
- B gas thread according to ISO 228
- Other materials on request (nickel-plated brass, stainless steel, etc.)

### ► Packaging:

- In bags
- Other packaging types on request

### ► Assembly:

UMM fittings can be used with flat-seat female fittings: P and RCP

### ► Sealing:

Flat gasket on flat seat

### ► Application:

All low-pressure applications



## ASSEMBLY

► IFT fittings must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"



## CUSTOM OFFER

► Contact us for all your specific requirements

### ► Fittings for your low-pressure applications / References & Compositions

Reference	Material	A thread		B thread	
		mm	inches	mm	inches
UMM0LAG	Brass	8 x 13	1/4"	8 x 13	1/4"
UMM10LAG		12 x 17	3/8"		1/4"
UMM1LAG		12 x 17	3/8"	12 x 17	3/8"
UMM21LAG		15 x 21	1/2"		3/8"
UMM2LAG		15 x 21	1/2"	15 x 21	1/2"
UMM42LAG		20 x 27	3/4"		1/2"
UMM4LAG		20 x 27	3/4"	20 x 27	3/4"
UMM52LAG		26 x 34	1"	15 x 21	1/2"
UMM54LAG		26 x 34	1"	20 x 27	3/4"
UMM5LAG		26 x 34	1"	26 x 34	1"
UMM65LAG		33 x 42	1" 1/4		1"
UMM6LAG		33 x 42	1" 1/4	33 x 42	1" 1/4
UMM76LAG		40 x 49	1" 1/2		1" 1/4
UMM7LAG		40 x 49	1" 1/2	40 x 49	1" 1/2
UMM87LAG		50 x 60	2"		1" 1/2
UMM8LAG		50 x 60	2"	50 x 60	2"