# UMF fitting Male-Female Flat-seat union





### **▶** Composition:

- Brass
- Gas thread according to ISO 228
- Other materials on request (nickel-plated brass, stainless steel, etc.)

# Packaging:

- In bags
- Other packaging types on request

## ▶ Assembly:

UMF fittings can be used with flat-seat fittings: P, M, MC and RCP

# ▶ Sealing:

Flat gasket on flat seat

### ► Application:

All low-pressure applications



➤ IFT fittings must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"



Contact us for all your specific requirements

# ▶ Fittings for your low-pressure applications / References & Compositions

Reference	Material	Male thread		Female thread	
		mm	inches	mm	inches
UMF01LAG	Brass	8 x 13	1/4"	12 x 17	3/8"
UMF0LAG				8 x 13	1/4"
UMF10LAG		12 x 17	3/8"	8 x 13	1/4''
UMF12LAG				15 x 21	1/2"
UMF1LAG				12 x 17	3/8"
UMF21LAG		15 x 21	1/2"	12 x 17	3/8"
UMF24LAG				20 x 27	3/4"
UMF2LAG				15 x 21	1/2"
UMF42LAG		20 x 27	3/4"	15 x 21	1/2"
UMF45LAG				26 x 34	1"
UMF46LAG				33 x 42	1"1/4
UMF4LAG				20 x 27	3/4"
UMF54LAG		26 x 34	1"	20 x 27	3/4"
UMF56LAG				33 x 42	1"1/4
UMF5LAG				26 x 34	1"
UMF64LAG		33 x 42	1"1/4	20 x 27	3/4"
UMF65LAG				26 x 34	1"
UMF67LAG				40 x 49	1"1/2
UMF6LAG				33 x 42	1"1/4
UMF75LAG		40 x 49	1"1/2	26 x 34	1"
UMF76LAG				33 x 42	1"1/4
UMF78LAG				50 x 60	2"
UMF7LAG				40 x 49	1"1/2
UMF87LAG		50 x 60	2"	40 x 49	1"1/2
UMF8LAG				50 x 60	2"



IFT Groupe Omerin SAS
Zone Industrielle – F 63600 Ambert
Tel: +33 (0)4 73 82 32 33
ift@omerin.com

80